

Recomendaciones de Condensadores Electrolíticos (de Partida)

ELAN



ELAN μF/250 Vac.	Uso recomendado	B.M.I. μF/125 Vac.
	1/8 HP	72/86
	1/6 HP	88/106
	1/6 HP	108/130
	1/4 HP	124/149
	1/4 HP	130/156
	1/3 HP	145/174
	1/3 HP	161/193
	1/3 HP	189/227
75	1/2 HP	216/259
	1/2 HP	233/280
75 - 100	3/4 HP	270/324
	3/4 HP	324/389
100 - 150	1.0 HP	340/408
	1.0 HP	378/454
	1.0 HP	400/480
150 - 200	1.5 HP	430/516
	1.5 HP	460/552
	2.0 HP	540/648
150 - 250	2.5 HP	590/708
200 - 300	3.0 HP	708/850
250 - 350	3.0 HP	800/960

B | M | I



*** Esta tabla solo es referencial y en ningún caso reemplaza la indicación de condensador de cada fabricante, consulte el manual o la placa del motor antes de comprar. ***

[ZENTENO N° 1464 – SANTIAGO](http://www.elanelectric.cl)

 +56 2 2555 2877 – +56 2 2555 9471 -
  +56 9 4437 9667

 ventas@elanelectric.cl – elanelectric@gmail.com

WWW.ELANELECTRIC.CL